




Guangdong Meijiaxin Innovative Technology Co., LTD

H8E Specification sheet

Basic product information		Product Photo	
Item No.	H8E		
color available	orange		
scale	1/8		
Max speed (low speed mode)	2S 7.5km/h		
	3S 11km/h		
Max speed (high speed mode)	2S 17km/h		
	3S 25km/h		
R/C distance	≥120m		
Product Size & Spec			
Product size(mm)	680×298×255		
Wheelbase(mm)	373		
Wheel track(mm)	240		
Tire Diameter(mm)	135	Crawl function configuration	
Vehicle weight	4.9KG	Gate bridge	included
Configuration		Gear	2 gear ratio, remote control metal steering gear switch
Motor	3970 2000KV Sensored Brushless Motor	Differential gear	Front/rear differential
ESC	80A FOC Sensored Brushless ESC	Differential lock	Front/rear differential gear , remote control steering gear switch
Servo	35KG steering servo	Reverse transmission	included
Receiver/Tranmitter transmission frequency	2.4Ghz	Linkage mechanism	4 link + tail watt link
Remote contoller	8CH	Servo Location	on bridge
Remote controller battery required	AA*3 (not included)	what's included in the box	
Battery & Charging cable	NOT INCLUDED	Truck (with remote controller) *1; manual * 1; Hexagon wrench * 1; Screw driver * 1;	
Packing data			
package	color box		
QTY/CTN(pcs)	1PCS		
color box size (cm)	77X 37.5 X 33.5cm		
Carton size (cm)	78.5X 38.5 X 34.5cm		
Gross weight/net weight(KG)	G.W: 9.2 KG, N.W: 7.9KG		
More photos for reference			
